

Text for invitation to tender the lift toilet CARE

Pos.	Text for invitation to tender the lift toilet CARE	price	total
	Lift-toilet Description: <i>CARE</i> The flush-mounted toilet unit is electrically adjustable from 400 to 750 mm in height. Integrated flushing tank, water saving flush plate with, color white. Ergonomically shaped foldable handles with integrated controls.		
	Technical specifications: Dimensions: 1410x608 mm Weight: 40 kg Height adjustment: 400-750 mm Max. load toilet bowl: 1,35 kN Max. load handles: 1,5 kN Water consumption (flushing): 6-9 Liter Connection (water): G1/2", G3/8" angle valve Connection (drain): DN110-as /high temperature tube flush with the wall. 230 mm from ground to top		
	Electrical specifications: <u>Linear motor</u> : 24 V DC, Power P1 = 0,08 kW <u>Power supply</u> : 220 - 230 V / 50 Hz, ELCB protect switch 30 mA, 16 A, IP 00 rating		
	Product information: Fixed and mobile concealed frame made of galvanized steel profiles. Interior parts of steel and danamid cover made of ABS plastic. Color: white		
	Accessoires: <u>Foldable handles with integrated controls / 700 mm / ergonomically shaped / spring-loaded</u> Dextral <input type="checkbox"/> Sinistral <input type="checkbox"/>		
	Colors: RAL-Colors		